

Production Painter's Tape

UTILITY GRADE PAPER MASKING TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Moisture-resistant crepe paper masking tape with a stain resistant pressure-sensitive rubber adhesive specially designed to stick firmly and securely to rough/uneven surfaces. Clean removal within 24 hours. Can withstand temperature up to 150°F (66°C).

PRODUCT APPLICATION

For residential and commercial painting. Interior paint masking, spray painting (air-dry). For hanging poly or paper draping. Compatible for use on lacquer or polyurethane-coated surfaces, unfinished wood or painted wallboard and trim. Can also be used for light bundling/ packaging, splicing and tabbing.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Coarse Crepe
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	38 (10.4 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	22 (96.3 N/25mm)
Elongation (% at break) PSTC-131	8
Total Thickness (mils) PSTC-133	5.2 (0.13mm)
Quick Stick (oz/in of width) PSTC-5	
To Steel	16.8 (4.6 N/25mm)
To Kraft	5.6 (1.5 N/25mm)
Temperature Operating Range	+40°F ~ +150°F (+4°C ~ +66°C)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
 Customer Service: 800.IPG.8273 | 800.474.8273
 Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/16

