

# Rubber Tape

## SELF-AMALGAMATING RUBBER TAPE

### DESCRIPTION

30 mil (0.76mm) self-amalgamating rubber, low-voltage electrical insulating tape. UL approved for use as primary insulation not exceeding 600 volts. Easily conforms to irregular shapes and surfaces for a void-free electrically stable build-up. Compatible with all extruded cable insulations. Resistant to water, oils, acids, alkalis and other corrosive chemicals.

### PRODUCT APPLICATIONS

For insulating splices on solid dielectric cable thru 600 volts in conjunction w/ jacketing tape. Repair frayed electrical wiring and general purpose maintenance repair.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/20

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Self-amalgamating Rubber
<b>Color</b>	Black
<b>Dielectric Strength</b> UL-510	350 volts (max) per mil
<b>Flammability</b> UL-510	Pass
<b>Tensile Strength</b> (p.s.i.) UL-510	250
<b>Elongation</b> (% at break) UL-510	300
<b>Total Thickness</b> (mils) UL-510	30 (0.76mm)
<b>Temperature Resistance</b> UL-510	Max. 176°F (80°C)
<b>Weather Resistance</b> UL-510	Pass

