

Storage Tape

1.85 MIL ACRYLIC CST

DESCRIPTION

Tough, impact resistant biaxially-oriented polypropylene (BOPP) film, coated with pressure-sensitive emulsion acrylic adhesive.

Best suited for reliable, all-temperature box sealing performance (less than 40°F and greater than 120°F) where resistance to aging, weathering, UV light, and yellowing are important. Provides excellent clarity, high shear strength to prevent 'flagging,' superior quick-stick performance, and controlled unwind.

PRODUCT APPLICATION

Light to medium weight non-critical box sealing applications exposed to minimal shipping hazards and stress.

GOVERNMENT COMPLIANCE

Conforms to the requirements of UPS, Parcel Post Air Freight and Motor Freight Classification Rule 222, and complies with the Federal Food Drug and Cosmetic Act, CFR Title 21, Subpart B, Par 175.105, which covers the use of pressure sensitive adhesives and tapes for indirect contact food packaging, such as box sealing.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing (Blown Film)	1.0 mil (0.025mm)
Adhesive	Emulsion Acrylic
Tensile Strength (lb/in width) ASTM D3759	25 (438 N/100mm)
Elongation (% at break) ASTM D3759	80
Adhesion to Steel (oz/in) ASTM D3330	17 (18.6 N/100mm)
Total Thickness (mils)	1.85 (0.047mm)
Application Temperature Range	+32°F to +150°F (0°C ~ +65°C)
Operating Temperature Range	-30°F to +200°F (-35°C ~ +93°C)
Colors	Clear, Tan

