

BUTYL MASTIC FOIL TAPE

Introducing a new addition to the IPG® line of HVAC solutions! ALF Mastic foil tape is a 17 mil, low VOC, aluminum foil pressure sensitive mastic sealant tape for indoor and outdoor use. It provides an instant water resistant grip to most surfaces required in HVAC applications and performs well within a wide temperature range. ALF Mastic foil tape features an easy release liner, and for best results should be applied with an IPG squeegee.

FEATURES & BENEFITS

- Instant waterproof grip that forms a permanent seal
- Excellent conformability with no cracking
- High weather, UV and temperature resistance
- · High resistance to mold and mildew
- Paintable
- LEED points contributor
- Hand tearable













PRODUCT ATTRIBUTES

CHARACTERISTICS		
ADHESIVE	Modified Butyl Rubber	
BACKING	Aluminum	
PEEL STRENGTH	>10 lbs/linear inch	
TENSILE STRENGTH	955 psi	
SERVICE TEMPERATURE	-20°F to +180°F (-28.9°C to +82°C)	
APPLICATION TEMPERATURE	+35°F to +110°F (-1.7°C to +43°C)	
TOTAL THICKNESS	17 (0.43mm)	
COLOR	Metallic	

ALF MASTIC

RESOURCE NUMBER	IMPERIAL SIZE	METRIC SIZE	CASE QUANTITY
99631	48mm x 30.4m	1.88in x 100ft	12
99632	72mm x 30.4m	2.88in x 100ft	12

GOVERNMENT COMPLIANCE

Tested in Accordance with UL-723 Seal Class A VOC Limitation SCAQMD Rule 1168 City of Los Angeles Approval RR#8069

PRODUCT APPLICATIONS

• For use on sheet metal, duct board, flex duct, PVC coated duct, and duct wrap vapor barriers

MARKETS

HVAC





