

i tape



PE34

UV-RESISTANT POLYETHYLENE MASKING

PE34 is a high tack polyethylene film stucco tape designed to mask surfaces and seam poly sheeting during outdoor stucco application and painting. This hand-tearable stucco tape offers 30-day UV resistance and is engineered with an aggressive synthetic adhesive that can keep a water-tight seal around windows and doors during the most severe weather conditions and demanding environments. PE34 is highly conformable and adheres well to a variety of surfaces such as wood, masonry, metals, vinyl, stucco and painted surfaces with clean removal.



FEATURES & BENEFITS

- 30 day UV-resistant
- Highly conformable
- High Tack
- Hand tearable
- Maintains watertight seal
- Clean removability
- Adheres well to polyethylene



©2019 Intertape Polymer Group • PE34-SS • 051319



888-898-7834 | itape.com



PRODUCT ATTRIBUTES

Style	Backing	Adhesive	Thickness	Adhesion to Steel	Tensile Strength	Elongation	Application Temp. Range	Operating Temp. Range	Color
			mils (mm)	oz/in (N/25mm)	lbs/in (N/25mm)	% at break			
PE34	PE film	Synthetic Rubber	7.0 (0.178)	75 (21)	21 (92)	75	+45°F to +120°F (+7°C ~ +49°C)	+20°F ~ +200°F (-7°C ~ +93°C)	Red

PRODUCT APPLICATIONS

- Masking Surfaces during stucco & painting
- Seaming poly sheeting
- Bonds well to a variety of substrates
- Green house repair

MARKETS

- Stucco/Construction
- Painting/Construction
- Asbestos Abatement
- Containment
- Restoration
- Storage/Preservation
- Manufactured Housing
- Foundation Seaming
- General Duct
- Screen Printing
- Agriculture Supply
- General Maintenance



Scan for more info or visit itape.com/petape

