PG20

30 DAY UV-RESISTANT PREMIUM PAPER MASKING TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

A black saturated crepe paper backing protects the specially formulated, high temperature resistant, pressure-sensitive natural rubber adhesive from the effects of ultraviolet light. Can be used in outdoor applications for periods of up to one (1) month depending on the weather conditions and the surface to which the tape is applied.

PRODUCT APPLICATION

Windshield repair/replacement for automotive, truck, bus and marine; automotive assembly plant applications.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.

ipg intertape polymer group

www.itape.com | info@itape.com

100 Paramount Drive, Suite 300 | Sarasota, FL $\,$ 34232 | USA $\,$

Customer Service: 800.IPG.8273 | 800.474.8273 Tape Technical Service: 877.447.4832

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/23

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Black Crepe Paper

Adhesive Natural Rubber/Resin

Adhesion to Steel (oz/in of width) 30 (8 N/25mm)

Tensile Strength (lbs/in of width) 23 (101 N/25mm)

Elongation (% at break) 8

Total Thickness (mils) 6.8 (0.17mm)

Quick Stick (oz/in of width)

To Kraft 7 (1.9 N/25mm)
To Steel 16 (4.4 N/25mm)

Operating Temperature Range 50°F ~ 325°F (10°C ~ 163°C)

Color Black

