

111

SINGLE LINER HAND-CUT STENCIL

DESCRIPTION

Hand-cut, high quality, durable stencil coated with an advanced medium tack, rubber-based pressure-sensitive adhesive protected by an easy-release-treated HDPE liner. Unique rubber formula allows easy cutting with less frequent knife sharpening. Controlled shrinkage gives accurate panel replacement after frosting.

PRODUCT APPLICATIONS

Designed for superior shape carving in marble and granite. Recommended for maximum depth glass etching. For optimum performance, use with #211 Stencil Filler.

STANDARD SIZES:

12.75" x 10 yards
18.75" x 10 yards
21" x 10 yards
25" x 10 yards
30" x 10 yards
30.5" x 10 yards

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/22

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	48 (1.22 mm)
Tensile Strength (lbs/in) PSTC-131	6 (26.28 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	50 (13.69 N/25mm)
Elongation (% at break) PSTC-131	400
Punch	Unpunched, Hand Cut
Liner Color	White
Recommended Filler	#211



ANCHOR
brand stencil products