

# 117

## SINGLE LINER MEDIA BLAST STENCIL – COMPUTER CUT

### DESCRIPTION

Computer cut, high quality, durable stencil coated with an advanced, medium tack, rubber-based pressure-sensitive adhesive protected by a clear polyester liner. Designed for precision cutting in slot-hole pattern Gerber® 15" and 30" plotters. The 15" widths will also track accurately in IBM® pattern and friction-fed cutters.

### PRODUCT APPLICATIONS

#117 is designed and recommended for use on polished granite or marble, primed/painted wood, and HDU foam-board. Replacement for #111 in Gerber® plotter applications. Excellent choice for deep sandblast etching of glass. For optimum performance on stone, use with #211 stencil filler.

### STANDARD SIZES

15" x 10 yds  
30" x 10 yds

### STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/22

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Adhesive</b>	Medium Tack / Rubber
<b>Total Thickness</b> (mil) PSTC-133	40 (1.02 mm)
<b>Tensile Strength</b> (lbs/in) PSTC-131	5 (21.9 N/25mm)
<b>180° Adhesion to Steel</b> (oz/in) PSTC-101	55 (15.06 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	375
<b>Punch</b>	Slot
<b>Liner Color</b>	Clear
<b>Recommended Filler</b>	#211

