

BD23

CREPE PAPER TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A medium strength, smooth crepe paper, pressure-sensitive tape having excellent tear strength and conformability to irregular surfaces. BD23's stain free adhesive is formulated to provide resistance to elevated temperatures (up to 300°F). Time of exposure and temperatures will vary depending on surfaces and application conditions.

PRODUCT APPLICATIONS

Product is recommended for bandoliering, tape and reeling of electronic components.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine Structured Crepe Paper
Adhesive	High Temperature Rubber/Resin
Adhesion to Steel (oz/in)	27 (7.4 N/25mm)
Quick Stick (oz/in)	17 (4.7 N/25mm) to steel 5 (1.4 N/25mm) to kraft
Tensile Strength (lbs/in)	24 (105 N/25mm)
Elongation (% at break)	9
Thickness (mils)	7.5 (0.191mm)
Colors	Natural



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/23

