

Performance Sheeting

PLASTIC SHEETING FILM

DESCRIPTION

A high performance, tear-resistant, and easily workable plastic sheeting film. This transparent, high density plastic film clings to substrates to provide surface protection and can help maintain a clean work environment.

PRODUCT APPLICATION

Used during repairs, this product protects vehicles from overspray and other potential contaminants.

STORAGE & SHELF LIFE

Shelf life is nine (9) months from date of manufacture.

IPG®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---------------------------|--------------------------------|
| Gauge | 0.3 mil |
| Backing | Polyethylene sheeting/film |
| Tensile D882 | 2000 psi (TD) 3000 psi (MD) |
| Elongation D882 | 250% (TD) 100% (MD) |
| Tear D1922 | 80g (TD) 5g (MD) |
| Color | Clear/Transparent |



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/25

