

# 99151

## HIGH TEMP PREMIUM PAPER MASKING TAPE

### DESCRIPTION

99151 is a mint green colored, conformable, saturated, crepe paper masking tape with pressure-sensitive rubber adhesive. Good adhesion and holding properties. Clean, easy removal. Unwind is very smooth. Resists paint flaking and performs well during wet sanding. Compatible with both water and solvent-based paints. UV-resistant up to three (3) days. Temperature resistant up to 300°F (149°C) for 30 minutes.

### PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.

### STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/23

IPG®

## TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Mint Green Crepe Paper
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width)	28 (7.6 N/25mm)
<b>Tensile Strength</b> (lbs/in of width)	22 (96.2 N/25mm)
<b>Elongation</b> (% at break)	10
<b>Total Thickness</b> (mils)	6.0 (0.15mm)
<b>Quick Stick</b> (oz/in of width)	
To Kraft	7 (1.9 N/25mm)
To Steel	16 (4.4 N/25mm)
<b>Color</b>	Mint Green

