



PALISADE® BUILDING ENVELOPE SYSTEM: AIR & MOISTURE MANAGEMENT SOLUTIONS

SYNTHETIC UNDERLAYMENT



SA-HT SELF-ADHERED UNDERLAYMENT



BUTYL HT SELF-ADHERED UNDERLAYMENT



800-565-2000 | roofunderlayment.com



PALISADE® SYNTHETIC UNDERLAYMENT



Patented* Stronghold Skid Resistant Technology® delivers superior walking & roof loading traction



Lighter weight & easier-to-handle rolls
10-square roll = 37 lbs



UV exposure up to 6 months before final roof covering is applied



Shingle blow-offs & fastener tear aways are reduced thanks to increased nail pull strength



Unique KOOL BLUE™ color technology produces lower heat & lower glare



Palisade® meets or exceeds the following building codes:

ASTM D8257



PALISADE® SA-HT




Patented* Stronghold Skid Resistant Technology® delivers superior walking & roof loading traction



High nail tear strength woven PP facer vs. film facer



UV exposure up to 6 months before final roof covering is applied



High temperature (250°F) adhesive formulated for superior high temperature performance



Unique KOOL BLUE™ color technology produces lower heat & lower glare



Palisade® SA-HT meets or exceeds the following building codes:

ASTM D-1970



PALISADE® BUTYL HT



Patented* Stronghold Skid Resistant Technology® delivers superior walking & roof loading traction



Wide temperature performance



UV exposure up to 6 months before final roof covering is applied



Better adhesion at lower temps & better stability at higher temps



Unique KOOL BLUE™ color technology produces lower heat & lower glare



Palisade® Butyl HT meets or exceeds the following building codes:

ASTM D-1970